FURGUT

Pressure/Vacuum Pump Model Series 90SL

DC Powered Rotary Vane Pumps, Gas Flow to 13 LPM **DESCRIPTION**

These rotary vane pumps are an excellent pressure/vacuum source for gas analyzers, medical devices, process samplers and other analytical instrument applications. They are also useful for material handling and many general automation applications.

The pumps are quiet, reliable and mount in any position. The units operate oil free. The pump vanes have a service life of 1,000 hours and are easily field replaced without special tools.




FEATURES

- Quiet operation
- Oil-free
- Easy maintenance

APPLICATIONS

- Gas analyzers
- Medical devices

FLOW RATE PERFORMANCES



500

mbar

SPECIFICATIONS

GENERAL

| Maximum Differential Pressure | 1700 mbar |
|-------------------------------|---------------------------|
| Maximum Flow | 13 LPM |
| Vane Material | Carbon |
| Media | Inert non-explosive gases |

Note:

** Operation at a somewhat lower than pump design voltage will yield a significantly longer life of the motor and the pump while also decreasing the current draw and operating noise of the unit.

** If used for continuous operation, we recommend selection of a pump that has a slightly higher pumping capacity than needed during normal operation.



-500

2,00


Drive Hud


1000

1500

2000

Hudson, MA 01749 Tel. 800 / 253 2497





ORDERING INFORMATION

| Model/ | Nominal | Voltage | Max. Flow | Vacuum | | | | Pressure | | | | Weight |
|------------|---------|---------|-----------|---------|-----|--------|-------|----------|------|----------|-------|--------|
| Order Code | Current | (V) | (L/min) | Current | | Vacuum | Noise | Cur | rent | Pressure | Noise | (kg) |
| | (A) | | | Min | Max | (mbar) | Level | Min | Max | (mbar) | Level | |
| | | | | (A) | (A) | | (dBA) | (A) | (A) | | (dBA) | |
| DC12/90SL | 2.7 | 12.0 | 13.0 | 1.6 | 3.0 | 810 | 84 | 2.2 | 7.6 | 1500 | 71 | 0.79 |
| No. 15988 | | 9.0 | 9.9 | 1.3 | 3.1 | 790 | 81 | 1.8 | 5.4 | 1100 | 74 | |
| | | 6.0 | 6.3 | 1.1 | 2.8 | 690 | 73 | 11 | 3.4 | 700 | 69 | |
| DC24/80L | 1.2 | 24.0 | 10.5 | 0.7 | 1.2 | 810 | 82 | 0.7 | 3.2 | 1700 | 71 | |
| No. 16987 | | 18.0 | 8.3 | 0.6 | 1.0 | 760 | 79 | 0.6 | 2.4 | 1200 | 65 | |
| | | 12.0 | 5.0 | 0.4 | 0.9 | 650 | 73 | 0.5 | 1.6 | 900 | 59 | |